

# LIGHTING SOLUTIONS FOR CONTROLLED ENVIRONMENT

## LED LINE SURFACE MOUNTED RPSM 300 600 2 x 2200 lm



conform with  Zhaga



## Applications

Environmentally controlled areas

## Specifications

### Design

Surface mounted luminaire specifically designed for controlled areas.

The specific design of this lighting fixture with half convex-shaped profile is only 28 mm high, standard with integrated driver.

Non visible fixing onto ceiling.

The joint frame-ceiling can easily be siliconed.

Allows easy cleaning. Tempered glazing.

### Body and frame

Aluminium extruded profile/plate, backplate zinc coated CRCA steel sheet, finished in epoxy polyester powder coated of 70-80 micron thickness.

### Standard colour

White

### Connector

3 way PUSH FIT connector

### Voltage

230 Volts AC - other voltages upon request

### LED

OSRAM PrevaLED® Linear Slim - 4000 K

Lifetime >50000 Hr

Output 137 lm/W

### IP-rating

IP 65 (bottom)

### Weight

4,35 kg.

### Options

1. Dimmable
2. Integrated emergency pack (1-3 hrs)
3. 1300 lm ledstrips
4. 1\*2200 lm ledstrip integrated
5. different colour temperature (K)
6. Separate box driver/emergency pack

### Garantee

OSRAM 5 year warranty



+ 32 (0)56 70 11 60  
www.rematcra.be

**LED LINE**  
**SURFACE MOUNTED**  
**RPSM 300 600**  
 2 x 2200 lm

