

LIGHTING SOLUTIONS FOR CONTROLLED ENVIRONMENT

LED LINE
SURFACE MOUNTED
RPSM 600 600
3 x 2200 lm



conform with  Zhaga



Applications

Environmentally controlled areas

Specifications

Design

Surface mounted luminaire specifically designed for controlled areas.

The specific design of this lighting fixture with half convex-shaped profile is only 28 mm high, standard with integrated driver.

Non visible fixing onto ceiling.

The joint frame-ceiling can easily be siliconed.

Allows easy cleaning. Tempered glazing.

Body and frame

Aluminium extruded profile/plate, backplate zinc coated CRCA steel sheet, finished in epoxy polyester powder coated of 70-80 micron thickness.

Standard colour

White

Connector

3 way PUSH FIT connector

Voltage

230 Volts AC - other voltages upon request

LED

OSRAM PrevaLED® Linear Slim - 4000 K

Lifetime >50000 Hr

Output 139 lm/W

IP-rating

IP 65 (bottom)

Weight

6.9 kg

Options

1. Dimmable
2. Integrated emergency pack (1-3 hrs)
3. 1300 lm ledstrips
4. different colour temperature (K)

Garantee

OSRAM 5 year warranty



+ 32 (0)56 70 11 60
www.rematcra.be

LED LINE
SURFACE MOUNTED
RPSM 600 600
 3 x 2200 lm

